

List of exhibits

1 Introduction

Exhibit 1 Summary of changes resulting in the HFDS	1-8
--	-----

2 General design requirements

(This section has no exhibits)

3 Automation

Exhibit 3.11 Levels of automation, from high to low	3-22
---	------

4 Designing equipment for maintenance

Exhibit 4.2.2.1 Maximum weight limits for objects lifted by one person using both hands	4-6
Exhibit 4.2.5.1.5 Maximum force limits for pulling and pushing units of equipment using handles or grasp areas	4-9
Exhibit 4.2.5.3.1 Minimum handle dimensions	4-11
Exhibit 4.2.5.3.2 Minimum handle diameter required by weight of unit of equipment	4-12
Exhibit 4.3.5.3.1 Minimum character height for various viewing distances	4-24
Exhibit 4.3.5.5.2 Recommended colors	4-26
Exhibit 4.3.5.5.3 Good and bad arrows	4-26
Exhibit 4.4.3.2 Minimum dimensions of openings designed for access by one or two fingers without visual access	4-28
Exhibit 4.4.3.3 Minimum dimensions of openings designed for access by one hand or arm without visual access	4-29
Exhibit 4.4.3.4 Minimum dimensions of openings designed for access by two hands without visual access	4-30
Exhibit 4.5.1.2 Type of covering for type of access and environmental conditions	4-34
Exhibit 4.6.3.3.2 Examples of combination-head bolts and screws	4-45
Exhibit 4.6.3.3.4 Example of an internal-wrenching bolt and nut	4-46
Exhibit 4.7.2.4 Example of a quick-action connector	4-53
Exhibit 4.7.5.2.2 Example of a crimp-on splice	4-57
Exhibit 4.7.5.2.5 Examples of a U-lug and an O-lug	4-57
Exhibit 4.8.1.1.5 Fanning out cables	4-60
Exhibit 4.8.1.1.13 Cable winder	4-61
Exhibit 4.8.1.2.6 Recoiling slack cable	4-63
Exhibit 4.8.1.5.3 Quick-release clamps, hinged and spring	4-66
Exhibit 4.8.1.6.6 An example of a line and cable reel car	4-67
Exhibit 4.8.1.6.8 Line and cable mobile support	4-68
Exhibit 4.8.1.8.4 Electrical cable coding	4-70
Exhibit 4.8.2.4.7 Externally visible seals	4-74
Exhibit 4.8.2.5.1 Color-coding of fluid conductors	4-75
Exhibit 4.8.2.5.2. Valve color-coding scheme	4-76
Exhibit 4.8.2.5.3 Hydraulic and pneumatic line color-coding scheme	4-77
Exhibit 4.8.2.5.5 Value position labeling	4-78
Exhibit 4.9.4.1 Example of foldout mounting construction	4-85
Exhibit 4.9.4.7 Error-free mounting provisions	4-86
Exhibit 4.11.1.1 General comparison of fuses and circuit breakers	4-92
Exhibit 4.11.3.1 Push-pull circuit breaker specifications	4-94

Exhibit 4.11.4.1	Toggle bat specifications	4-95
Exhibit 4.11.4.2	Legend switch specifications	4-96
Exhibit 4.12.2.13	Terminal strips	4-99
Exhibit 4.12.4.4 (a)	Test plug with sliding cover	4-101
Exhibit 4.12.4.4 (b)	Test point adapter	4-101

5 Displays and printers

Exhibit 5.1.2.7	Display face not tilted more than 45° to user's line of sight	5-3
Exhibit 5.1.2.10	Optimum vertical and horizontal visual fields	5-4
Exhibit 5.3.3	Stroke width for pixel-generated characters	5-14
Exhibit 5.3.4	Height-width relationship for upper case pixel-generated characters	5-14
Exhibit 5.3.8	Example of positive and negative polarity	5-15

6 Controls and visual indicators

Exhibit 6.1.1.1.5 (a)	Characteristics of common controls for continuous adjustments	6-2
Exhibit 6.1.1.1.5 (b)	Characteristics of common controls for continuous adjustments	6-3
Exhibit 6.1.1.3.8	Minimum spacing between controls	6-5
Exhibit 6.1.1.4.1	Advantages and disadvantages of different types of coding	6-6
Exhibit 6.1.2.3.1	Minimum character height for various viewing distances under normal luminance levels	6-14
Exhibit 6.1.4.1	Foot-operated switch specifications	6-19
Exhibit 6.1.5.1.5	Rotary selector switch	6-21
Exhibit 6.1.5.2.1	Key-operated switch specifications	6-25
Exhibit 6.1.5.4.1	Knob Specifications	6-27
Exhibit 6.1.5.5.1	Ganged control knob specifications	6-29
Exhibit 6.1.5.5.7	Relationship between ganged knobs and their associated visual indicators	6-30
Exhibit 6.1.5.6.1	Continuous thumbwheel specifications	6-31
Exhibit 6.1.5.7.1	Crank specifications	6-32
Exhibit 6.1.5.8.1	Push button specifications	6-34
Exhibit 6.1.5.9.1	Toggle switch specifications	6-36
Exhibit 6.1.5.10.1	Legend switch specifications	6-38
Exhibit 6.1.5.11.1	Rocker switch specifications	6-40
Exhibit 6.1.5.12.1	Slide switch specifications	6-42
Exhibit 6.1.5.13.1	Push-pull control specifications	6-48
Exhibit 6.1.5.16.1	Hand-force hand control specifications	6-50
Exhibit 6.2.2.1.8	Optimum vertical and horizontal visual fields	6-55
Exhibit 6.2.2.1.27	Color-coding of transilluminated displays	6-58
Exhibit 6.2.2.3.3	Coding of simple indicator lights	6-61
Exhibit 6.2.5	Characteristics and ratings for direct-reading counters, printers and flags	6-64
Exhibit 6.2.6.1	Characteristics and ratings of fixed and moveable pointer scales for various uses	6-67

7 Alarms, audio, and voice

Exhibit 7.2.1.7	Characteristics and ratings of audio signals for various uses	7-6
Exhibit 7.4.1.2	Speech intelligibility criteria for voice communication systems	7-17

8 Computer-human interface

Exhibit 8.2.2.1	Luminance contrast ratios for various conditions	8-7
Exhibit 8.3.3.1.4	Examples of acceptable and unacceptable patterns.....	8-39
Exhibit 8.3.3.1.5	Example of axes with breaks	8-40
Exhibit 8.6.2.5.2	Color combinations to avoid	8-60
Exhibit 8.7.6.2.5	Mnemonics and accelerators	8-89
Exhibit 8.13.5.12	Example of a default push button	8-120
Exhibit 8.13.10.5.6	Example of better and worse pointing cursors	8-129
Exhibit 8.13.10.6.5	Pointer shapes associated with functions	8-131
Exhibit 8.15.6.1.2	Maximum system response times for routine system tasks....	8-166

9 Input devices

Exhibit 9.0	Advantages and disadvantages of non-keyboard input devices.....	9-1
Exhibit 9.0 (cont.)	Advantages and disadvantages of non-keyboard input devices ..	9-2
Exhibit 9.0 (cont.)	Advantages and disadvantages of non-keyboard input devices ..	9-3
Exhibit 9.1.15	Cursor movement keys.....	9-5
Exhibit 9.3.2.5	Dimensions of a mouse.....	9-9
Exhibit 9.3.3.3.1	Finger-operated displacement joystick specifications.....	9-12
Exhibit 9.3.3.7.1	Ball control specifications.....	9-15
Exhibit 9.3.6.1	Pointer shapes associated with functions.....	9-19
Exhibit 9.4.2.4	Touch panel responsive area dimensions	9-24

10 Workstation and Workplace design

Exhibit 10.2.1.1 (a)	Standard console dimensions.....	10-3
Exhibit 10.2.1.1 (b)	Standard console illustration and dimension key	10-4
Exhibit 10.2.2.2.	Seated workspace dimensions and illustrations	10-7
Exhibit 10.2.2.13	Swing-away seat for short-term use	10-9
Exhibit 10.2.3	Example of horizontal wrap-around console.....	10-10
Exhibit 10.2.4	Examples of vertical stacked segments.....	10-11
Exhibit 10.2.5.1	Basic and variations of multi-person console arrangements with an example control room.....	10-14
Exhibit 10.2.5.2	Concepts of functional reach arc and equidistant visual arc for a stand console.....	10-15
Exhibit 10.2.6.1	Standing workstation illustration and dimensions consoles where see over capabilities are not required	10-18
Exhibit 10.2.10.1	Dimensions and illustrations for workspaces other than seated or standing.....	10-21
Exhibit 10.3.2.4	Access space through integral design.....	10-25
Exhibit 10.4.1.2	Walkway and passageway	10-27
Exhibit 10.4.2.6	Minimum clearance point for a single wheelchair	10-28
Exhibit 10.4.2.7	Dimensions for making a U-turn in a wheelchair.....	10-29
Exhibit 10.4.7.2.1	Door dimensions	10-34
Exhibit 10.4.7.6.1	Whole body access dimensions.....	10-38
Exhibit 10.4.8.1.2	Type of structure in relation to angle of ascent.....	10-39
Exhibit 10.4.8.1.12	Critical dimensions for ramps	10-41
Exhibit 10.4.8.1.15	Combined ramp and stairs.....	10-42
Exhibit 10.4.8.3.1	Design requirements for stair dimension.....	10-44
Exhibit 10.4.8.4.1	Design requirements for stair ladders.....	10-46
Exhibit 10.4.8.5.1	Design requirements for fixed ladders	10-48
Exhibit 10.4.8.5.3	Design requirements for fixed ladder cage dimensions.....	10-49
Exhibit 10.4.8.6.1 (a)	Design requirements for portable step ladders.....	10-50

Exhibit 10.4.8.6.1 (b) Design requirements for portable rung ladders.....	10-51
11 System security	
(This section has no exhibits)	
12 Personnel safety	
Exhibit 12.2.1.8 Specific task illumination requirements.....	12-4
Exhibit 12.4 Shock current intensities and their effects	12-7
Exhibit 12.4.1.3 Proof test values for protective gloves	12-9
Exhibit 12.4.1.9 An interlock switch.....	12-10
Exhibit 12.4.3.3 Automatic shorting bar	12-13
Exhibit 12.4.4.6 Equipment grounding.....	12-14
Exhibit 12.5.1.4 (a) Rolling edges of sheets less than 0.5 mm (0.02 in) thick.....	12-17
Exhibit 12.5.1.4 (b) Rounding exposed edges 0.5 up to 3.0 mm (0.02 up to 0.12 in) thick	12-17
Exhibit 12.5.1.4 (c) Rounding exposed edges 3.0 to 6.4 mm (0.12 up to 0.12 in) thick	12-17
Exhibit 12.5.1.4 (d) Rounding of exposed edges 6.4 mm (0.25 in) thick or greater	12-17
Exhibit 12.5.1.5 (a) Requirements for rounding of corners less than 25 mm (1.0 in).....	12-18
Exhibit 12.5.1.5 (b) Requirements for rounding of corners greater than 25 mm (1.0 in).....	12-18
Exhibit 12.10.1 Upper and lower temperature limit range.....	12-24
Exhibit 12.12.8 Permissible noise exposure	12-28
Exhibit 12.14.1.1 Exposure limit for ultraviolet radiant energy (200 to 315 nm)	12-30
Exhibit 12.14.3 Relative contribution of different wavelengths to luminance.....	12-32
Exhibit 12.14.3.1 Maximum safe exposure to 400 - 1400 nm radiant energy	12-32
Exhibit 12.14.3.4 Estimation of permissible image luminance	12-33
Exhibit 12.16.2 Label and placard layout – two panel sign with optional symbol pane	12-36
13 Environment	
Exhibit 13.2.3 Large enclosure ventilation.....	13-3
Exhibit 13.3 Comfort zone chart	13-5
Exhibit 13.3.1 Deriving effective temperature	13-6
Exhibit 13.4.2.2 Specific task illumination requirements.....	13-11
Exhibit 13.4.2.2 (continued) Specific task illumination requirements.....	13-12
Exhibit 13.4.6.3 Required brightness ratios.....	13-16
Exhibit 13.5.1.1 Permissible exposure limits.	13-18
14 Anthropometry and biomechanics	
Exhibit 14.1.4.4 Additive effects of clothing on anthropometric measures.....	14-9
Exhibit 14.1.4.4 (continued) Additive effects of clothing on anthropometric measures	14-10
Exhibit 14.1.5.1 Percentile values	14-11
Exhibit 14.3.2.1 Static human physical characteristics (head)	14-15
Exhibit 14.3.2.1 (continued) Static human physical characteristics (head)	14-16
Exhibit 14.3.2.1 (continued) Static human physical characteristics (head)	14-17
Exhibit 14.3.2.1 (continued) Static human physical characteristics (head)	14-18
Exhibit 14.3.2.1 (continued) Static human physical characteristics (seated).....	14-19
Exhibit 14.3.2.1 (continued) Static human physical characteristics (seated).....	14-20
Exhibit 14.3.2.1 (continued) Static human physical characteristics (seated)....	14-21

Exhibit 14.3.2.1 (continued) Static human physical characteristics (seated).....	14-22
Exhibit 14.3.2.1 (continued) Static human physical characteristics (standing)	14-23
Exhibit 14.3.2.1 (continued) Static human physical characteristics (standing)	14-24
Exhibit 14.3.2.1 (continued) Static human physical characteristics (standing)	14-25
Exhibit 14.3.2.1 (continued) Static human physical characteristics (hand)	14-26
Exhibit 14.3.2.1 (continued) Static human physical characteristics (standing position).	14-27
Exhibit 14.3.3.2.1 Joint movement ranges.....	14-30
Exhibit 14.3.3.2.1 (continued) Joint movement ranges	14-31
Exhibit 14.3.3.2.1 (continued) Joint movement ranges	14-32
Exhibit 14.3.3.2.2 Change in range of joint movement with movement in an adjacent joint	14-34
Exhibit 14.4.2 Reach envelopes in vertical and horizontal plane	14-36
Exhibit 14.4.3 (a) Touch, grip, and grasp functions.	14-37
Exhibit 14.4.3 (a) (continued) Touch, grip, and grasp functions	14-38
Exhibit 14.4.3 (b) Thumb and forefinger grasp boundary data for females in the 46 cm and 61 cm horizontal planes	14-40
Exhibit 14.5.2.1 Male muscle strength of the arm, hand, and thumb for control forces (5 th percentile values)	14-44
Exhibit 14.5.2.1 (continued) Design criteria for male muscle strength of the arm, hand, and thumb for control forces (5 th percentile values)	14-45
Exhibit 14.5.3.1 Horizontal push and pull forces that can be exerted	14-47
Exhibit 14.5.3.2 Static muscle strength data for vertical pull exertions.....	14-49
Exhibit 14.5.3.2 (continued) Static muscle strength data for vertical pull exertions	14-50
Exhibit 14.5.3.2 (continued) Static muscle strength data for vertical pull exertions	14-51
Exhibit 14.6.1 Forward reach from a wheelchair.....	14-52
Exhibit 14.6.1 (continued) Forward reach from a wheelchair	14-53
Exhibit 14.6.4 Side reach from a wheelchair.....	14-53
Exhibit 14.6.6 Wheelchair dimensions	14-54

15 User documentation

Exhibit 15.4 FAA directives and order of document components	15-33
Exhibit 15.4.1.2 Type sizes for cover page elements.....	15-34
Exhibit 15.4.12.3 (a) User feedback form – Front	15-47
Exhibit 15.4.12.3 (b) User feedback form – Back	15-48